

DSR Series Fluorescent Soft Light



- Soft, even, smooth light field free of exposure of heat from the beam emission.
- High light output from the luminaries with high efficiency reflector and barn door.
- High color rendering index (CRI up to 85-95). Optimum effects shall be expected when the luminary use halogen lamps.
- High illumination of lamp tubes (70-80 lumens/watt) and longer lamp life (imported lamps rated more than less than 10000 hours).
- Energy-saving components utilized to save electrical energy by 70%.
- Lamp holders mounted meet international safety standards; imported electronic ballasts are used for lower noise and reliable operations.
- Added dimming function optional with imported ballasts enabling a wide dimming range while maintaining a constant color temperature.
- Ideal for lighting applications for medium and small-sized studios and conference rooms as well as news studios.

Specification:

| Item No. | Power Input | Spigot | Wattage | Color Temperature | Dimming | Dimensions | Weights |
|------------|---------------------|--------|---------|-------------------|-------------|---------------|---------|
| DSR 36x2 | AC 100-240V,50/60Hz | Φ28x75 | 72W | 3200°K/5600°K | | 480x240x150mm | 4.75Kg |
| DSRIV 36x2 | AC 100-240V,50/60Hz | Φ28x75 | 72W | 3200°K/5600°K | Dimmer Rack | 480x240x150mm | 4.77Kg |
| DSR 36x4 | AC 100-240V,50/60Hz | Φ28x75 | 144W | 3200°K/5600°K | | 480x365x150mm | 6.85Kg |
| DSRIV 36x4 | AC 100-240V,50/60Hz | Φ28x75 | 144W | 3200°K/5600°K | Dimmer Rack | 480x365x150mm | 6.87Kg |
| DSR 36x6 | AC 100-240V,50/60Hz | Φ28x75 | 216W | 3200°K/5600°K | | 480x520x150mm | 9.30Kg |
| DSRIV 36x6 | AC 100-240V,50/60Hz | Φ28x75 | 216W | 3200°K/5600°K | Dimmer Rack | 480x520x150mm | 9.32Kg |
| DSR 55x2 | AC 100-240V,50/60Hz | Φ28x75 | 110W | 3200°K/5600°K | | 605x240x150mm | 5.70Kg |
| DSRIV 55x2 | AC 100-240V,50/60Hz | Φ28x75 | 110W | 3200°K/5600°K | Dimmer Rack | 605x240x150mm | 5.72Kg |
| DSR 55x4 | AC 100-240V,50/60Hz | Φ28x75 | 220W | 3200°K/5600°K | | 605x365x150mm | 7.90Kg |
| DSRIV 55x4 | AC 100-240V,50/60Hz | Φ28x75 | 220W | 3200°K/5600°K | Dimmer Rack | 605x365x150mm | 7.92Kg |
| DSR 55x6 | AC 100-240V,50/60Hz | Φ28x75 | 330W | 3200°K/5600°K | | 605x645x150mm | 10.40Kg |
| DSRIV 55x6 | AC 100-240V,50/60Hz | Φ28x75 | 330W | 3200°K/5600°K | Dimmer Rack | 605x645x150mm | 10.42Kg |